iV.

Docket No.: INA-0005

AMENDMENTS TO THE CLAIMS

- 1. (Original) A sterilizer comprising:
- a hopper in which powders and grains are filled;
- a first rotary valve disposed under said hopper; and
- a second rotary valve formed under said first rotary valve,

wherein an airtight space, allowing therethrough travel of said powders and grains, is formed between said first rotary valve and said second rotary valve, said airtight space being communicated with a saturated steam injection pipe injecting a saturated steam into said airtight space.

- 2. (Original) The sterilizer as claimed in Claim 1, wherein said first and second rotary valves are configured as being adjustable in the rotating speeds, and configured as rotating in directions reverse to each other.
- 3. (Original) The sterilizer as claimed in Claim 1 or 2, further comprising a drier which includes:

an inclined plate group in which plates on one side inclined in one direction, and plates on the other side inclined in the other direction, receiving the powders and grains dropped from said plates on one side, are disposed as being alternately staggered, with a large number of fine perforations formed therein; and

a heating air supplier supplying upward a heating air from the lower side of said inclined plate group.

- 4. (Original) The sterilizer as claimed in Claim 3, wherein said Inclined plate group is configured as being adjustable in the angle of inclination of each of said plates.
- 5. (Currently Amended) The sterilizer as claimed in Claim 3-or 4 further comprising a cooler disposed on the lateral of said inclined plate group, said cooler including:

Application No. Not Yet Assigned Amendment dated September 28, 2006 First Preliminary Amendment

υλů

Docket No.: INA-0005

an inclined plate group in which plates on one side inclined in one direction, and plates on the other side inclined in the other direction, receiving the powders and grains dropped from said plates on one side, are disposed as being alternately staggered, with a large number of fine perforations formed therein; and

a cooling air supplier supplying upward a cooling air from the lower side of said inclined plate group.